LABDEX

Portable Autoclave LX103POA

Email: info@labdex.com **website:** www.labdex.com

Description

Portable autoclave LX103POA is an advanced steam sterilizer and a portable N class unit with a capacity of 18 L and a sterilizing temperature of 126 °C. It can effectively sterilize media, liquids and waste to be removed. An Electric heated and dual scale pressure gauge indicator.

Specifications

Volume of Chamber	18 L (280 x 260 mm)
Working temperature	126 ℃
Heating mode	Electrically heated
Working pressure	0.14 ~ 0.16 Mpa
Max safety pressure	0.165 Mpa
Heat average	≤ ± 1℃
Temp adjustment	105 ~ 126 ℃
Power	AC 220 V / 50 Hz / 2 KW
Overall Dimension	410 × 410 × 520 mm
Net Weight	16 Kg
Gross Weight	18 Kg

Features

- Sterilizing Temperature 126 °C
- Dual scale pressure gauge indicator
- Equipped with pressure and overheating warning indicator
- Chambers formation with stainless steel
- Leak-proof chamber with self–inflating facility
- Electric heated
- Safe and reliable

Applications

- Used in Medical, Research Institutions, Laboratory, Drinking Water Plant, Food industry, Hospital, Agriculture, Hospital, Scientific Research.

71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.
Email: info@labdex.com | Website: www.labdex.com